

A standard linear barcode is positioned vertically on the right side of the page. It consists of vertical black bars of varying widths on a white background.

ISSUE CLASSIFICATION	
Class	Subclass

**PATENT NUMBER**

## **U.S. UTILITY Patent Application**

BK	O.I.P.E.	PATENT DATE
SCANNED <i>Am'</i>	Q.A. <i>LP</i>	

APPLICATION NO.	CONT/PRIOR	CLASS <del>375</del> 444	SUBCLASS 522	ART UNIT 263T	EXAMINER JO
09/751464	D				

Azeem Ahmad  
Ashvin Chheda

455

2684 Lee

TITLE

## Method and apparatus for fast forward-link power control and synchronization of base stations

PTO-2040  
12/99

## **ISSUING CLASSIFICATION**

Continued on Issue Slip Inside File Jacket

TERMINAL DISCLAIMER	DRAWINGS			CLAIMS ALLOWED	
	Sheets Drwg.	Figs. Drwg.	Print Fig.	Total Claims	Print Claim for O.G.
<input type="checkbox"/> The term of this patent subsequent to _____ (date) has been disclaimed.				<b>NOTICE OF ALLOWANCE MAILED</b>	
<input type="checkbox"/> The term of this patent shall not extend beyond the expiration date of U.S Patent. No. _____ _____ _____				<b>ISSUE FEE</b>	
	(Assistant Examiner)	(Date)	(Primary Examiner)	(Date)	Amount Due      Date Paid
<input type="checkbox"/> The terminal _____ months of this patent have been disclaimed.				<b>ISSUE BATCH NUMBER</b>	

**WARNING:**

The information disclosed herein may be restricted. Unauthorized disclosure may be prohibited by the United States Code Title 35, Sections 122, 181 and 368. Possession outside the U.S. Patent & Trademark Office is restricted to authorized employees and contractors only.

Form PTO-438A  
(Rev. 8/99)

FILED WITH:  DISK (CRF)  FICHE  CD-ROM  
(Attached in pocket on right inside flap)

BEST AVAILABLE COPY

(FACE)